

# F289

## STAR HANDWHEEL WITH STEEL HUB AND THREADED STUD



### Materials:

Reinforced polyamide.  
Resistant to oils and greases.

### Surface finish:

Satin.

### Colour:

Black (RAL 9011).




### Inserts:

**F289:**  
Galvanised steel insert with threaded stud (thread tolerance 6g).

**F289CIN:**  
Stainless steel insert with threaded stud (Aisi 303) (thread tolerance 6g).

### Special requests:

- Upon request and for special quantities inserts can be supplied with customised lengths.
- Upon request and for special quantities available in the colours indicated in the chart (attention: reduced range) [page ].



Version F289: Galvanised steel hub.

| Code | Art.             | D  | d  | d2 | H  | m  | c  | d1 <sub>6g</sub> | Q    | LM | g  |
|------|------------------|----|----|----|----|----|----|------------------|------|----|----|
| -    | F28940.TM08X2001 | 40 | 14 | 16 | 24 | 12 | 12 | M8               | 20   | 55 | 38 |
| -    | F28950.TM10X4001 | 50 | 18 | 20 | 29 | 15 | 14 | M10              | A.R. | 60 | 60 |
| -    | F28960.TM12X2501 | 60 | 20 | 24 | 34 | 18 | 16 | M12              | 25   | 60 | 97 |

Customised stud lengths available for a minimum of 150 pieces.

LM = Maximum mouldable length.

Version F289 CIN: Stainless steel hub (Aisi 303).

INOX

| Code | Art.                | D  | d  | d2 | H  | m  | c  | d1 <sub>6g</sub> | Q  | LM | g  |
|------|---------------------|----|----|----|----|----|----|------------------|----|----|----|
| -    | F28940.TM08X2001CIN | 40 | 14 | 16 | 24 | 12 | 12 | M8               | 20 | 55 | 38 |
| -    | F28950.TM10X4001CIN | 50 | 18 | 20 | 29 | 15 | 14 | M10              | 40 | 60 | 60 |
| -    | F28960.TM12X2501CIN | 60 | 20 | 24 | 34 | 18 | 16 | M12              | 25 | 60 | 97 |

Customised stud lengths available for a minimum of 150 pieces.

LM = Maximum mouldable length.

