K170

+135°∎ -30°C





LOBED HANDWHEEL FOR INDICATOR

Materials:

Reinforced polyamide. Resistant to oils and greases.

Surface finish:

Satin.

Colour:

(RAL 9011). Black

Mountable indicator:

Gravity position indicator model K650080. The indicator can be only used in a vertical position (horizontal machine axis). The indicator must be purchased separately. For further information see article K650 [page].

Galvanised steel insert with smooth through bore (tolerance H10) with key according to the dimension of the bore.

Indicator fixing method:

Fix the indicator with a threaded grub screw M05 (not supplied) to be inserted in the special bore M05.


Special Requests:


- On request and with a minimum of 50 pieces, the inserts can be supplied with the hole d1 with H7 tolerance and black-oxide finish.
- Upon request and for special quantities inserts can be $supplied\ with\ custom\ hole\ diameter\ d1.$
- Upon request and for special quantities inserts can be supplied in different materials.


Combinations Diameters/Indicators: d5=52.4 --> K650050 d5=87.4 --> K650080 or K660080











| Code | art. | D | Н | h | h1 | h2 | h3 | h4 | h5 | h6 | d | d2 | d3 | d4 | d5 | Α | В | d1 H10 | Q | ĝ |
|--------------|-------------------|-----|----|------|----|----|----|-----|----|----|----|----|----|------|-----|---|-----|---------------|----|-----|
| K170110 0001 | K170110 T80D1201H | 110 | 58 | 30.5 | 20 | 18 | 20 | 155 | 12 | 75 | 52 | 95 | 25 | 85.5 | 874 | 4 | 131 | 12 | 20 | 230 |

