

R101

POLYAMIDE MONOLITHIC WHEEL WITH ROUND STEEL SWIVEL SUPPORT AND SMOOTH THROUGH HOLE

Materials:

- Wheel body (1):**
Polyamide. Resistant to oils and greases.
- Tread (2):**
Polyamide. Resistant to oils and greases.

Surface finish:
Smooth.

Colour:
(1-2) Natural white.
(3-4-5-6) Galvanised blue.

Wheel rotation (4):
The hole for the pivot pin is formed by plastic moulding. A galvanised steel tube is positioned between the stud and the hole for protection.

Bracket (3):
Steel fork (DD13).


Rotating assembly (5):
Steel rotating assembly with double ball race and smooth fixing hole, (hole tolerance H7).

Wheel fastening (6):
Steel hex head screw, coupled with a steel nut.

- Special requests:**
- Upon request and for a minimum of 20 pieces, the wheel can be supplied with a needle roller cage, (replace code no. R101 with code no. R131).



18



Code	art.	D	A	H	I	d	d1H7		F1 (Kg)
R101080.0001	R101080.T30D12	80	30	108	32	64	12	360	100
R101100.0001	R101100.T30D12	100	30	127	32	64	12	400	130
R101125.0001	R101125.T39D12	125	39	155	32	64	12	726	130
R101150.0001	R101150.T40D12	150	40	184	35	65	12	-	140
R101175.0001	R101175.T45D16	175	45	228	48	95	16	-	270
R101200.0001	R101200.T50D16	200	50	240	48	95	16	1970	270