

R402

max

3 Km/h

+50°

- 5°

PP

TPE

UL94
HB

RoHS
COMPLIANT

POLYPROPYLENE / RUBBER WHEEL WITH ROUND STEEL SWIVEL SUPPORT AND SMOOTH THROUGH HOLE WITH BRAKE

Materials:
Wheel body:
Polypropylene.
Tread:
Synthetic thermoplastic rubber. Hardness 93 ± 3 Shore A.

Surface finish:
Smooth.

Colour:
(1) Black (RAL 9011).
(2) Light grey.
(3-4-5-6-7) Galvanised blue.

Wheel rotation (4):
The hole for the pivot pin is formed by plastic moulding. A galvanised steel tube is positioned between the stud and the hole for protection.

Bracket (3):
Steel fork (DD13), with integrated brake. Brake actuation lever moulded in grey plastic.

Rotating assembly (5):
Steel rotating assembly with double ball race and smooth fixing hole, (hole tolerance H7).

Wheel fastening (6):
Steel hex head screw, coupled with a steel nut.

Thread guards (7):
Sheared steel thread guard disk fixed on both sides.

Special requests:
• None.

18

Code	art.	D	A	H	I	d	F	d1H7		F1 (Kg)
R402050.0001	R402050.T18D12	50	18	70	26	48	80	12	-	40
R402063.0001	R402063.T22D12	63	22	90	26	48	84	12	-	60
R402080.0001	R402080.T22D12	80	22	109	25	48	84	12	-	60
R402100.0001	R402100.T27D12	100	27	134	36	57	106	12	-	80
R402125.0001	R402125.T27D12	125	27	159	35	57	106	12	-	80

BATECO
COMPONENTS

ver. 18V01-0124

768 ()