

POLYPROPYLENE / RUBBER WHEEL WITH ROUND STEEL SWIVEL SUPPORT AND THREADED STUD

Ruote in PP/Gomma sintetica (Colletività)

Materials:

Wheel body:

Polypropylene.

Tread:

Synthetic thermoplastic rubber. Hardness 93 ± 3 Shore A.

Surface finish:

Smooth.

Colour:

(1) Dark grey.

(2) Light grey.

(3-4-5-6-7) Galvanised blue.

Wheel rotation (4):

The hole for the pivot pin is formed by plastic moulding. A galvanised steel tube is positioned between the stud and the hole for protection.

Bracket (3):

Steel fork (DD13).

Rotating assembly (5):

Steel rotating assembly with double ball race and threaded stud (thread tolerance 6g).

Wheel fastening (6):


Steel hex head screw, coupled with a steel nut.

Special requests:

With a minimum of 100 pieces, M12 threaded studs can be supplied instead of M10, and vice versa.

Upon request the wheel can be supplied in material with high electrical conductivity (ESD).





Code	art.	D	A	H	I	d	d1 6g	Q	Weight (g)	F1 (Kg)
R603050.0001	R603050.T18M10X25	50	18	70	26	48	M10	25	-	40
R603063.0001	R603063.T22M10X25	63	22	90	26	48	M10	25	-	60
R603080.0001	R603080.T22M10X25	80	22	109	25	48	M10	25	-	60
R603100.0001	R603100.T27M12X30	100	27	134	36	57	M12	30	-	80
R603125.0001	R603125.T27M12X30	125	27	159	35	57	M12	30	-	80

Code	art.	D	A	H	I	d	d1 6g	Q	Weight (g)	F1 (Kg)
R603050.0002	R603050.T18M10X25ESD	50	18	70	26	48	M10	25	-	40
R603060.0001	R603060.T22M10X25ESD	60	22	90	26	48	M10	25	-	60
R603080.0002	R603080.T24M10X25ESD	80	24	109	25	48	M10	25	-	60
R603100.0002	R603100.T29M12X30ESD	100	29	134	36	57	M12	30	-	80
R603125.0002	R603125.T29M12X30ESD	125	29	159	35	57	M12	30	-	80