

KNOB WITH LOCKING STEEL INDEXING PLUNGER

Spintori filettati passo grosso - con pomello

Materials:

- (1) Stainless steel plunger pin (Aisi 303).
- (3) Stainless steel spring (Aisi 302).
- (4) Reinforced polyamide lobed knob. Cannot be disassembled. Resistant to oils and greases.

W793:

- (2) Locking indexing plunger body in free-cutting steel.

W793 CIN:

- (2) Stainless steel (Aisi 303) locking indexing plunger body.

Surface finish:

- (4) Satin.
- (1-2-3) Smooth.

Colour:

- (4) Black (RAL 9011).

W793:

- (2) Galvanised.

W793 CIN:

- (1-2) Natural.


ATTENTION:

- > We recommend an H7 tolerance for the plunger stem bore.

Special Requests:

None.





Version W793 - galvanised steel

Code	Art.	D	d	H	h	e	s	d2	d1 -0,02 -0,04	Q	Weight (g)
W793.0001	W793.J0401	14	7	36	12	6	8	M6	4	4	5
W793.0003	W793.J0501	18	9	46	16	8	10	M8	5	5	11
W793.0005	W793.J0601	22	11	55	20	10	11	M10	6	6	24
W793.0007	W793.J0801	21	12,5	64	20,5	12	14	M12	8	8	39

Version W793 CIN - stainless steel (Aisi 303)

Code	Art.	D	d	H	h	e	s	d2	d1 -0,02 -0,04	Q	Weight (g)
W793.0002	W793.J0401CIN	14	7	36	12	6	8	M6	4	4	5
W793.0004	W793.J0501CIN	18	9	46	16	8	10	M8	5	5	11
W793.0006	W793.J0601CIN	22	11	55	20	10	11	M10	6	6	24
W793.0008	W793.J0801CIN	21	12,5	64	20,5	12	14	M12	8	8	39